

OVERVIEW

# Domestic & Commercial Fans



VF-EF250



VF-N4



VF-Q4



VF-T6-1



VF-BV295-2



VF-BF1030



VF-TD6

### Introduction

SwiftFans Lite mission statement is to provide effective and aesthetically pleasing ventilation solutions, ease of installation, in a reliable, quality product.

The range consists of fans suitable for the most common mounting and application scenarios, complete with ancillaries to provide a one-stop-shop solution to almost any domestic and commercial ventilation requirement.

SwiftFans are designed to the highest efficiency, aesthetic, and noise standards.

### Quality

All processes, from component manufacture, to assembly and testing, are carried out in a ISO9001 accredited manufacturing facility.

### Motors

Motors are manufactured using silicon steel laminates and pure copper windings with bearings designed for long operational life.

A thermal cut-out device is fitted inside the motor windings to protect the motor.

### Fan casings & Impellers

Components are injection moulded using LG ABS plastic which provides superior impact resistance, has flame retardant properties, is UV resistant and has long lasting colour stability.

### Packaging

Our attractive branded packaging will compliment any retail store, and is manufactured using environmentally friendly and recyclable materials.



**OVERVIEW**

Model	Fan Type Axial = A Centrifugal = C Mixed flow = M	Wall	Glass	Ceiling	Gravity Shutter/s	Auto-shutter (Thermal Actuator)	Running Light Indicator	Switch operated	Two Speed	LED Light	Applications
VF-N4	A	•	•	•				•			Single toilet, bathroom, small room exhausting directly to outside or into ceiling space
VF-N6	A	•	•	•				•			Office, bathroom, kitchen, small room exhausting directly to outside or into ceiling space
VF-N8	A	•	•	•				•			Office, bathroom, kitchen, utility room exhausting directly to outside or into ceiling space
VF-T6-1	A	•	•			•	•	•			Office, bathroom, kitchen, small room exhausting directly to outside
VF-T9-1	A	•	•			•	•	•			Office, bathroom, kitchen, utility room exhausting directly to outside
VF-BF1030	C			•	•			•			Single toilet, bathroom, small room exhausting to outside via ducting
VF-BF1440	C			•	•			•			Office, bathroom, kitchen, utility room exhausting to outside via ducting
VF-EF250	A			•	•			•			Office, bathroom, kitchen, utility room exhausting directly into ceiling space
VF-BV295-2	C			•	•			•		•	Office, bathroom, kitchen, utility room exhausting to outside via ducting. Includes 14W LED light
VF-Q4	A	•	•	•		•		•			Single toilet, bathroom, small room exhausting directly to outside or into ceiling space
VF-Q6	A	•	•	•		•		•			Office, bathroom, kitchen, small room exhausting directly to outside or into ceiling space
VF-Q8	A	•	•	•		•		•			Office, bathroom, kitchen, utility room exhausting directly to outside or into ceiling space
VF-TD6	M							•	•		Ducted single point or multi-point ventilation systems
VF-TD8	M							•	•		Ducted single point or multi-point ventilation systems

Dimensions in mm

**OVERVIEW**

Model
<b>Fan Accessories</b>
Backdraught Shutter BS-4
Backdraught Shutter BS-5
Backdraught Shutter BS-6
Backdraught Shutter BS-8
Glass Mounting Ring GMR-4
Glass Mounting Ring GMR-6
Wall Mounting Kit WMK
<b>Outdoor Vents &amp; Shutters</b>
Gravity Shutter VF-GS4
Gravity Shutter VF-GS5
Gravity Shutter VF-GS6
Gravity Shutter VF-GS8
Fixed Grille VF-FS4
Fixed Grille VF-FS5
Fixed Grille VF-FS6
Fixed Grille VF-FS8
Air Vent SS304 VF-VL4
Air Vent SS304 VF-VL5
Air Vent SS304 VF-VL6
Air Vent SS304 VF-VL8
Round Air Vent White RS-4
<b>Air Valves &amp; Ceiling Grilles</b>
Air Valve Plastic VF-CAV4
Air Valve Plastic VF-CAV5
Air Valve Plastic VF-CAV6
Air Valve Plastic VF-CAV8
Round Air Grille White VF-CAG4
Round Air Grille White VF-CAG5
Round Air Grille White VF-CAG6
Round Air Grille White VF-CAG8

Note: Greyed out items not stocked.

<b>Duct &amp; Duct Accessories</b>
Bend 90° VF-BP90/4
Bend 90° VF-BP90/5
Bend 90° VF-BP90/6
Bend 90° VF-BP90/8
Y-Piece VF-YP4
Y-Piece VF-YP5
Y-Piece VF-YP6
Y-Piece VF-YP8
Hose Clamp HC-4
Hose Clamp HC-5
Hose Clamp HC-6
Hose Clamp HC-8
Aluminium Flexible Hose FH-4
Aluminium Flexible Hose FH-5
Aluminium Flexible Hose FH-6
Aluminium Flexible Hose FH-8
PVC Rigid Thin Wall Duct VF-RD4-350
PVC Rigid Thin Wall Duct VF-RD6-350
<b>Controllers</b>
Run-on Timer
Motion Sensor
Thermostat

For more information about fan selection, correct positioning of fans, and replacement air, please visit our website [www.cfw.co.za](http://www.cfw.co.za).

Dimensions in mm



[www.cfw.co.za](http://www.cfw.co.za)

Cape Town Head Office: Tel. +27 (0) 21 931 8331 | Johannesburg Tel: +27 (0) 11 452 5830/3/4